


WETLAND BUFFER RESTORATION PLAN


O MOUNTAIN ROAD, LOT 25-2, WILTON, CT

BY ALEKSANDRA MOCH LANDSCAPE DESIGNER, DECEMBER 21, 2023



PLANTING SCHEDULE

QTY	KEY	BOTANICAL/COMMON NAME	SIZE	ROOT
7	AC	Amelanchier canadensis / Serviceberry tree	5'-6'	Cont.
5	IG	Ilex glabra 'Compacta' / Inkberry	3'-4'	Cont.
11	CS	Cornus sericea / Red osier dogwood	3'-4'	Cont.
10	CO	Cephalanthus occidentalis / Buttonbush	3'-4'	Cont.
10	CA	Clethra alnifolia / Summersweet	2'-3'	Cont.
20	CL	Chasmanthium latifolium / Northern sea oats	#3	Cont.
20	MA	Matteuccia / Ostrich fern	#3	Cont.



-8" PROCESSED AGGREGATE

— COMPACTED SUBGRADE


DRIVEWAY PAVEMENT

NOT TO SCALE

24" SUMP

COARSE PARTICLE SEPARATOR

NOT TO SCALE



280

260

250

SILT FENCE TO COMPLETELY SURROUND DOWNGRADE

3' MINIMUM SPACE BETWEEN STOCKPILE AND SILT FENCES.

STOCKPILE PROTECTION

SIDE AND ENDS OF STOCKPILE AREA.

NOT TO SCALE

NDS, INC.

851 NORTH HARVARD AVE. LINDSAY, CA 93247

TOLL FREE: 1-800-726-1994

CONC./STONE PAVERS

BASE MATERIAL

PAVER SETTING BASE

REVISION DATE 8-24-2015

555

550

545

540

535

530

525

PHONE: (559) 562-9888

FAX: (559) 562-4488

www.ndspro.com

NDS SPEE-D CHANNEL DRAIN GRATE W/ U.V. INHIBITOR RECESS CHANNEL1/4" FROM TOP OF CONCRETE.

L_{4" NOM.} MONOLITHIC CONC POUR TO ENCASE CHANNEL

#3 REBAR x 12" LONG. TO SECURE LATERAL CHANNEL MOVEMENT @ BRICK LOCATIONS.

NDS SPEE-D CHANNEL DRAIN -

SPACED @ 36" O.C. TO ALLOW FOR CONC. UNDER CHANNEL.

NOTES:

1. EXISTING SOILS SHOULD BE EVALUATED TO ENSURE PROPER STRUCTURAL AND PERMEABILITY PROPERTIES.

SPEE-D CHANNEL DRAIN


LIGHT VEHICULAR TRAFFIC INSTALLATION (PAVERS)

1. EXISTING SOILS SHOULD BE EVALUATED TO ENSURE PROPER STRUCTURAL AND PERMEABILITY PROPERTIES.
2. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
3. DO NOT SCALE DRAWING.
4. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY.
5. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.

WIRE TIE AT REBAR STAKE LOCATION -TO CHANNEL (DRILL HOLE) TO ARREST VERTICAL MOVEMENT.


CONCRETE MIN. 4" DEPTH.


2168_231216Drainage




SLOPE LINE A: 3.5'/81.2' 4.3% 553.5 to 550.0 SLOPE LINE B: 3.7'/56.9' 6.5% 553.7 to 550.0 SLOPE LINE C: 5.6'/59.7' 9.4% 553.6 to 548.0

AVG. SLOPE 6.73%







NOT TO SCALE





SCALE- H: 1"-10'

V: 1"-5'















FINISH GRADE ---


TYPICAL CLEANOUT NOT TO SCALE




1500 GALLON PUMP CHAMBER NOT TO SCALE

65' OF GEOMATRIX GST 6218 CAPACITY = 899.6 GALLONS MAX. DOSE FOR 65' OF GEOMATRIX GST 6212 = 449.8 GALLONS/CYCLE DOSE PROPOSED = 150 GALLONS PER CYCLE PUMP CHAMBER CAPACITY = APPROX. 40.0 GALLONS/INCH DEPTH

PUMP 6" OFF BOTTOM = 240 GALLONS; CYCLE = 3.8" = 150 GALLONS; 1,110 GALLONS RESERVE 3 BEDROOMS X 150 GALLONS/DAY + 5 (75) = 825 GALLLONS LIBERTY 290 SERIES PUMP DELIVERS APPROX. 30 GALLONS/MIN.




Patents: www.geomatrixsystems.com GST is a trademark of Geomatrix Systems, LLC
March 2021 © All rights reserved



60 WINFIELD STREET, NORWALK, CONNECTICUT 06855 PH: (203) 831-8005 FAX: (203) 831-8006

2168_231216Septic



Existing Conditions









Routing Diagram for 2168ExistingRev1

Prepared by Fairfield County Engineering LLC, Printed 12/18/2023 HydroCAD® 10.00-26 s/n 06020 © 2020 HydroCAD Software Solutions LLC

Page 6

HydroCAD® 10.00-26 s/n 06020 © 2020 HydroCAD Software Solutions LLC


Summary for Subcatchment 1S: Existing Conditions


Runoff = 7.70 cfs @ 12.08 hrs, Volume= 0.551 af, Depth> 2.34"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs Type III 24-hr 25 Year Rainfall=6.50"

_	Α	rea (sf)	CN I	Description		
*	1	22,846	61	Woods, Fai	r, HSG B	
_	1	22,846		100.00% Pe	ervious Are	a
	Тс	Length	Slope	Velocity	Capacity	Description
_	(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
	5.0					Direct Entry, Direct

Subcatchment 1S: Existing Conditions





Proposed Conditions









Routing Diagram for 2168ProposedRev3

Prepared by Fairfield County Engineering LLC, Printed 12/18/2023 HydroCAD® 10.00-26 s/n 06020 © 2020 HydroCAD Software Solutions LLC


Summary for Subcatchment 2S: Proposed Conditions


Runoff = 9.09 cfs @ 12.08 hrs, Volume= 0.639 af, Depth> 2.72"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs Type III 24-hr 25 Year Rainfall=6.50"

	Are	a (sf)	CN	Description			
*	2	2,468	98	House			
*	Ę	5,115	98	Driveway			
*		525	98	Pool			
*	•	1,395	98	Patio			
	22,488 69 50-75% Grass cover, Fair, HSG B						
*	90	0,855	61	Woods, Fai	r, HSG B		
	122	2,846	65	Weighted A	verage		
	113	3,343		92.26% Per	vious Area		
	9,503 7.74% Impervious Area				ervious Area	a	
	Tc L	_ength	Slop	e Velocity	Capacity	Description	
_	(min)	(feet)	(ft/f	t) (ft/sec)	(cfs)		
	5.0					Direct Entry, Direct	

Subcatchment 2S: Proposed Conditions






Summary for Subcatchment 3S: Areas Routed to Retention

Runoff = 1.43 cfs @ 12.07 hrs, Volume= 0.106 af, Depth> 5.44"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs Type III 24-hr 25 Year Rainfall=6.50"

A	rea (sf)	CN	Description					
*	5,115	98	Driveway					
*	2,468	98	House					
	2,600	69	50-75% Grass cover, Fair, HSG B					
	10,183	91	Weighted A	verage				
	2,600		25.53% Pervious Area					
	7,583		74.47% Impervious Area					
Tc	Length	Slop	e Velocity	Capacity	Description			
(min)	(feet)	(ft/ft	:) (ft/sec)	(cfs)				
5.0					Direct Entry, Direct			

Subcatchment 3S: Areas Routed to Retention



yardor ib a force to an observation and contract conditions the


Runoff = 7.70 cfs @ 12.08 hrs, Volume= 0.545 af, Depth> 2.53"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs Type III 24-hr 25 Year Rainfall=6.50"

	Area (sf) C	ON D	escription				
*	5	25	98 P	ool				
*	1,3	95	98 P	Patio				
	19,8	88	69 50	50-75% Grass cover, Fair, HSG B				
*	90,8	55 (61 V	oods, Fai	r, HSG B			
	112,6	63 (63 W	eighted A	verage			
	110,7	43	98	3.30% Per	vious Area			
	1,9	20	1.	70% Impe	rvious Area	a		
	Tc Ler	ngth	Slope	Velocity	Capacity	Description		
_	(min) (f	eet)	(ft/ft)	(ft/sec)	(cfs)			
	5.0					Direct Entry, Direct		

Summary for Subcatchment 4S: Areas not Routed to Retention

Subcatchment 4S: Areas not Routed to Retention



Type III 24-hr 25 Year Rainfall=6.50"

Prepared by Fairfield County Engineering LLC
HydroCAD® 10.00-26 s/n 06020 © 2020 HydroCAD Software Solutions LLC

Printed 12/18/2023

Page 12

Summary for Pond 1P: Cultec R-280

Inflow Area =	0.234 ac, 74.47% Impervious, Inflow D	Depth > 5.44" for 25 Year event
Inflow =	1.43 cfs @ 12.07 hrs, Volume=	0.106 af
Outflow =	1.15 cfs @ 12.16 hrs, Volume=	0.106 af, Atten= 20%, Lag= 5.5 min
Discarded =	0.10 cfs @ 11.16 hrs, Volume=	0.090 af
Primary =	1.05 cfs @ 12.16 hrs, Volume=	0.016 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs Peak Elev= 541.42' @ 12.16 hrs Surf.Area= 700 sf Storage= 1,165 cf

Plug-Flow detention time= 78.1 min calculated for 0.106 af (100% of inflow) Center-of-Mass det. time= 77.8 min (855.1 - 777.3)

Volume	Invert	Avail.Storage	Storage Description
#1A	538.00'	254 cf	41.17'W x 17.00'L x 2.21'H Field A
			1,545 cf Overall - 911 cf Embedded = 635 cf x 40.0% Voids
#2A	538.00'	911 cf	Cultec R-280HD x 20 Inside #1
			Effective Size= 46.9"W x 26.0"H => 6.07 sf x 7.00'L = 42.5 cf
			Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
			Row Length Adjustment= +1.00' x 6.07 sf x 10 rows
		1,165 cf	Total Available Storage

Storage Group A created with Chamber Wizard

Device	Routing	Invert	Outlet Devices			
#1	Primary	540.20'	6.0" Horiz. Orifice/Grate	C= 0.600	Limited to weir flow at low heads	
#2	Discarded	538.00'	6.000 in/hr Exfiltration over Horizontal area			


Discarded OutFlow Max=0.10 cfs @ 11.16 hrs HW=538.02' (Free Discharge) **2=Exfiltration** (Exfiltration Controls 0.10 cfs)

Primary OutFlow Max=0.99 cfs @ 12.16 hrs HW=541.29' (Free Discharge) 1=Orifice/Grate (Orifice Controls 0.99 cfs @ 5.03 fps)

Printed 12/18/2023

Page 13

Pond 1P: Cultec R-280



Page 14

Summary for Link 1L: Combined Hydrograph


Inflow Area = 2.820 ac, 7.74% Impervious, Inflow Depth > 2.39" for 25 Year event

Inflow = 7.70 cfs @ 12.08 hrs, Volume= 0.562 af

Primary = 7.70 cfs @ 12.08 hrs, Volume= 0.562 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.04 hrs

Link 1L: Combined Hydrograph



DRAINAGE REPORT

PREPARED FOR

EXISTING AND PROPOSED SITE CONDITIONS

LOCATED AT:

0 MOUNTAIN ROAD

FCE #2168



WILTON, CONNECTICUT

December 16, 2023

FAIRFIELD COUNTY ENGINEERING, LLC

CIVIL ENGINEERS

60 WINFIELD ST.
NORWALK, CONNECTICUT 06855
(203) 831-8005
FAX: (203) 831-8006

E-mail to: wayne@fairfieldce.com



NARRATIVE:

The subject of this report is a 2.82 acre parcel located at 0 Mountain Road in Wilton. The purpose of this report is to determine the existing and proposed runoffs resulting from the proposed site improvements in order to design a stormwater management system.

EXISTING CONDITIONS:

The subject parcel is a rear lot located at the northwest side of Mountain Road, approximately 200 feet from its intersection with Indian Hill Road. The lot is currently vacant. The lot slopes moderately to steeply towards the wetlands centrally located on the property; from the north and south.

Existing soils at this location, as identified in the NRCS Soil Survey of Fairfield County, Connecticut, consist of Charlton-Chatfield complex, 0 to 15 percent slopes, very rocky, which has a Hydrologic classification of 'B'.

The existing runoff as developed from a 25-Year rainfall event is 7.70 c.f.s.

PROPOSED CONDITIONS:

The proposal for this site is to construct a new single family residence with associated driveway and pool.

The proposed runoff from a 25-Year rainfall event is 9.09 c.f.s.

COMPUTATIONS:

The following computations of the existing and proposed conditions runoff flows were derived from the HydroCAD computer software. HydroCAD follows the NRCS TR-20 procedure for computing stormwater runoff. Computations were performed for a 25-year storm event, which has a 4% chance of occurring in any given 12 month period.

Existing Conditions:

Woods 122,846 s.f. CN 61

Total - 122,846 s.f.

Weighted CN - 61

Proposed Conditions:

House	2,468 s.f.	CN 98
Driveway	5,115 s.f.	CN 98
Pool	525 s.f.	CN 98
Patio	1,395 s.f.	CN 98
Woods	90,855 s.f.	CN 61
Lawn	22,488 s.f.	CN 69

Total - 122,846 s.f.

Weighted CN - 65

Water Quality Volume

$$I = (7.7 \times 0.009) + 0.05 = 0.1193$$

 $WQV = (0.1193 (2.82 \text{ acres})/12) = 0.0280355 \text{ ac-ft} = 1,221.2 \text{ ft}^3.$

Groundwater Recharge Volume

 $GWV = 1,221.2 \times 0.25 = 305.3 \text{ ft}^3.$

SUMMARY

Existing Runoff (25 Year): 7.70 c.f.s.

Proposed Runoff (25 Year): 9.09 c.f.s.

Proposed Impervious Run-off 1.43 c.f.s

Retained (25 Year):

Proposed Run-off from Areas 7.70 c.f.s.

Bypassing Retention plus overflow (25 Year):

CONCLUSIONS:

The increased runoff resulting from the proposed site improvements will be retained in an on-site retention system. The runoff from the house roof, driveway and a portion of the lawn will be routed to 20 units of Cultec R-280 retention chambers.

This system will maintain the net peak runoff during a 25 Year storm at its current peak of 7.70 c.f.s.

The proposed retention system provides 1,165 ft³ of storage, which will accommodate the runoff from a 25 Year rainfall event routed to the system, and provides groundwater recharge.

The proposed improvements will have no adverse impact on surrounding properties.

NEW ENGLAND WETLAND PLANTS, INC.

SEED MIX PRICING SHEET

SHADE LOVING MEADOW MIX-202	23-DEC
-----------------------------	--------

TOWN OF GREENWICH				12	2/19/2023
Application Rate lbs/acre	25				
Minimum Quantity Required	10				
Approximate Seeds/ft2	383				
Price (\$ Per Pound)	\$160.98				
Total FOB	\$1,609.81				
Shipping and Handling Est	\$24.00				
Total Cost	\$1,633.81				<u>Approx</u>
Botanical Name	Common Name	Indicato	<u>% By</u> or Weight	Approx Seed/ft2	<u>% by</u> <u>Seed</u> Count
Festuca arundinacea	Tall Fescue (n)	FACU	20.00%	24	6.27%
Elymus hystrix	Bottlebrush Grass		20.00%	9	2.35%
Carex grayi	Gray's Sedge	FACW+	13.00%	1	0.26%
Elymus villosus	Silky Wild Rye	FACU-	10.00%	5	1.31%
Carex scoparia	Blunt Broom Sedge	FACW	5.00%	39	10.18%
Anemone virginiana	Thimbleweed/Tall Anemon	e FACU	2.00%	5	1.31%
Aquilegia canadensis	Eastern Columbine	FAC	2.00%	6	1.57%
Lobelia siphilitica	Great Blue Lobelia	FACW+	2.00%	89	23.24%
Eupatorium rugosum (Ageratina altissima)	White Snakeroot	FACU-	2.00%	28	7.31%
Geum canadense	White Avens	FACU	1.00%	2	0.52%
Solidago caesia	Blue Stem/Woodland Goldenrod	FACU	1.00%	4	1.04%
Juncus tenuis	Path Rush	FAC	1.00%	166	43.34%
Clematis virginiana	Virgin's Bower	FAC	1.00%	1	0.26%
Aster divaricatus(Eurybia divaricata)	White Wood Aster	5	1.00%	4	1.04%
			81.00%	383	100.00%