

Floodlights
with mounting canopy or 1/2" IPS nipple


A series of compact rectangular floodlights with mounting canopy or 1/2" IPS nipple. Available in various sizes and distributions this family of luminaires sets the floodlighting standard with regards to cost effectiveness, compactness and efficiency.

Die-cast aluminum - Safety glass - Reflector made of pure anodized aluminum
LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidue® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available PAL and custom colors, are a polyester powder.

NRTL listed to North American standards - Suitable for wet locations
Protection class IP 65



1/2" IPS nipple
Accessories for mounting
surface mounted conduit
wing box and 19594
available in wiring box
website.



Outrigger arm and mounting box
Accessories for mounting
surface mounted conduit
wing box and 19594
available in wiring box
website.



Floodlights with mounting canopy - very wide

	LED	β	A	B	C	D	
84507	9.8 W	78/90°	6 1/2	7 1/4	3 1/2	4	70500
77538	17.6 W	75/85°	6	7 1/4	3 1/2	4	70500
77539	23.6 W	82/93°	9	8 1/4	4	4	70502
77582	65.6 W	82/93°	11 1/2	10 1/2	5	4	70525



Floodlights with mounting canopy - flat beam

	LED	β	A	B	C	D	
84510	9.8 W	29/37°	6 1/2	7 1/4	3 1/2	4	70500
77536	17.6 W	29/36°	6	7 1/4	3 1/2	4	70500
77537	23.6 W	39/54°	9	8 1/4	4	4	70502
77584	65.6 W	32/55°	11 1/2	10 1/2	5	4	70525



Floodlights with 1/2" IPS nipple - very wide

	LED	β	A	B	C	
84509	9.8 W	78/90°	6 1/2	7 1/4	3 1/2	70500
77479	17 W	75/85°	6 1/2	7	3 1/2	70500
77486	23.6 W	87/93°	9	8 1/4	4	70502
77427	65.6 W	82/93°	11 1/2	10 1/2	5	70525



Floodlights with 1/2" IPS nipple - flat beam

	LED	β	A	B	C	
84511	9.8 W	29/37°	6 1/2	7	3 1/2	70500
77480	17.6 W	29/36°	6 1/2	7 1/4	3 1/2	70500
77485	27.6 W	39/54°	9	8 1/4	4	70502
77434	65.6 W	32/54°	11 1/2	10 1/4	5	70525

180° glass shield β=Beam angle

